



US005768003A

United States Patent [19]

Gobeli

[11] Patent Number: **5,768,003**[45] Date of Patent: **Jun. 16, 1998**[54] **SPATIAL LIGHT MODULATOR AND METHOD**[75] Inventor: **Garth W. Gobeli**, Albuquerque, N. Mex.[73] Assignee: **Complex Light Valve Corporation**, Albuquerque, N. Mex.[21] Appl. No.: **555,494**[22] Filed: **Nov. 8, 1995**[51] Int. Cl.⁶ **G02F 1/03**[52] U.S. Cl. **359/254; 359/322**[58] Field of Search **359/252, 254, 359/322, 323, 258, 255**[56] **References Cited****U.S. PATENT DOCUMENTS**

3,940,201	2/1976	Micheron et al.	359/254
3,955,190	5/1976	Teraishi	340/336
4,053,207	10/1977	Keve et al.	350/150
4,379,621	4/1983	Ikeda et al.	350/392
4,793,697	12/1988	Wu et al.	350/393
4,816,381	3/1989	Kaukeinen	430/319
4,867,543	9/1989	Bennion et al.	350/384
4,990,943	2/1991	Phillips	350/392

5,198,920	3/1993	Gobeli	359/245
5,221,989	6/1993	Stappaerts et al.	359/323
5,260,719	11/1993	Maloney	346/107

OTHER PUBLICATIONS

"Photoconductive Activated Light Valve for High Definition Projection System", by Garth Gobeli and Thomas Toor, SPIE vol. 1664 High-Resolution Displays and Projection Systems (1992), pp. 172-176.

Primary Examiner—David C. Nelms

Assistant Examiner—Dawn-Marie Bey

[57] **ABSTRACT**

A spatial light modulator including a thin layer of solid-state electro-optical material having parallel, opposite first and second surfaces, an elongated first electrode disposed on the first surface and a plurality of spaced, elongated second electrodes disposed on the second surface and generally perpendicular to the first electrode. The layer of solid-state electro-optical material has a thickness in the range of approximately 5 to 15 microns, and is composed of PLZT. In one embodiment, a plurality of thin regions of insulator are disposed on the first surface between portions of the first electrode and the electro-optical material.

14 Claims, 3 Drawing Sheets

